



AEROFLEX®

Special Purpose Contact Adhesive



Aeroseal

Professional / Industrial Grade
Contact Adhesive



AEROFLEX®

Aeroseal BLACK
Contact Adhesive

282 Industrial Park Road - Sweetwater, TN 37874
Phone: 1-866-AEROCEL (237-6235) - Fax: 877-337-7675
Website: www.aeroflexusa.com

Important Notice:
This contact adhesive is for professional and industrial use only. The Consumer Product Safety Commission prohibits the sale of this adhesive to consumers for personal use in containers exceeding 1/2 pint.

Warning:
Hazardous when used as directed. Do not use in areas where it will be in contact with food, drink, or other consumables. Do not use in areas where it will be in contact with electrical equipment.

1/2 Pint (0.42 lb. / 192 g)

AEROFLEX®

Brush-Top Aeroseal
Contact Adhesive

282 Industrial Park Road - Sweetwater, TN 37874
Phone: 1-866-AEROCEL (237-6235) - Fax: 877-337-7675
Website: www.aeroflexusa.com

Important Notice:
This contact adhesive is for professional and industrial use only. The Consumer Product Safety Commission prohibits the sale of this adhesive to consumers for personal use in containers exceeding 1/2 pint.

1 Pint (0.8 lb. / 384 g)

AEROFLEX

Aeroseal
Contact Adhesive

282 Industrial Park Road - Sweetwater, TN 37874
Phone: 1-866-AEROCEL (237-6235) - Fax: 877-337-7675
Website: www.aeroflexusa.com

Warning:
Hazardous when used as directed. Do not use in areas where it will be in contact with food, drink, or other consumables. Do not use in areas where it will be in contact with electrical equipment.

1 Pint (0.8 lb. / 384 g)



Aeroseal

Professional / Industrial Grade
Contact Adhesive

HVAC | Refrigeration | VRF | Chilled Water
Duct Liner | Ductwrap | Hot & Cold-Water Piping

Fast tack, solvent-based, special-purpose contact
adhesive specially formulated for bonding adjoining
seams of Aerocel® insulation to suitable substrates.

Colors: Amber and Black

Sizes: 1 gallon, 1 quart, 1 pint w/ brush-top,
1/2 pint w/ brush-top

Fast, simple to install

Fast tack times of 1-3 minutes (depending on ambient conditions)

Instantly bonds once dry to the touch

Tapes and coatings can be applied immediately after installation

Superior performance

Strong permanent bonds

High water vapor resistance

Properly sealed seams minimize likelihood of corrosion under
insulation (CUI)




Aeroflex insulation system solutions



Aerofix®

Light-weight, rigid pipe supports, pre-insulated with closed-cell EPDM foam rubber and encased with zero-perm EPDM polymer membrane. Includes built-in pressure sensitive Protape® closure system.



Protape®

Zero-perm, EPDM-based, self-adhering rubber tape for sealing adjoining seams and termination points.



Aerocoat™

A premium specialty coating for exterior weather protection and as a decorative finish.



Aerocoat LVOC™

A low-VOC UV protective coating, best choice for LEED® projects.

Product: Modified neoprene solvent-based contact adhesive for bonding Aerocel insulation to itself and to suitable substrates such as clean metal.

Application: Stir contents thoroughly before use. Do not thin. Apply thin even coat to both clean and dry surfaces with short-bristle brush or adhesive roller. Allow short tack time (1-3 minutes or more depending on ambient conditions) until dry to the touch (no transfer) before applying both glued surfaces together. The bond is immediate with no adjustability. Moderate pressure should be applied over the entire area to ensure complete contact and a vapor seal.

Aeroseal should be applied when ambient and surface temperatures are above 40°F (4°C) and below 100°F (38°C). Do not allow to freeze.

If adhesive was dry to the touch prior to contact, glued seams may be covered with Protape® and full-coverage applications may be coated with Aerocoat™ or Aerocoat LVOC™ immediately after installation.

Clean Up: Use acetone to clean adhesive residue from tools.

Physical Properties

Composition (Amber or Black)	Synthetic rubber base with added resins and fillers
Solids Content	Approximately 25% by weight
Net Weight	6.9 lbs/gal
VOC Content	417 g/L
Service Temperature Range	-20°F to 257°F (piping), 200°F (sheets & rolls) -28°C to 125°C (piping), 93°C (sheets & rolls)
Flame Spread/Smoke-Developed Index	10/0 (ASTM E 84, UL 723)
Tack Time	1-3 minutes (dry to touch, no transfer)
Dry Time	Immediate (upon contact)
Coverage	Up to 200 ft ² /gal
Shelf Life	1 year (store at 60°F (16°C) - 80°F (27°C))

Read all warnings on product label before use.



282 Industrial Park Road Sweetwater, TN 37874
423.337.2493 Fax: 423.337.7675 Toll Free: 866.AEROCEL
www.aeroflexusa.com

111521