

Outside Diameters for Jacketing AEROFLEX EPDM™ Pipe Insulation

AEROFLEX	THICKNESS						
	1/4"	3/8"	1/2"	3/4"	1"	1-1/2"	2"
Label ID	Total OD (in)	Total OD (in)	Total OD (in)	Total OD (in)	Total OD (in)	Total OD (in)	Total OD (in)
1/4"	.95*	1.15*	1.35*	1.85	2.40	3.55*	N/A
3/8"	1.08*	1.28	1.48	1.98	2.53	3.68	4.73*
1/2"	1.23*	1.43	1.63	2.13	2.68	3.83	4.88
5/8"	1.36*	1.56	1.76	2.26	2.86	3.96	5.01
3/4"	1.48*	1.68	1.88	2.38	2.98	4.08	5.13
7/8"	1.59*	1.79	2.05	2.61	3.09	4.29	5.34
1-1/8"	1.84*	2.04	2.30	2.86	3.34	4.54	5.59
1-3/8"	N/A	2.34	2.66	3.24	3.64	4.84	5.89
1-5/8"	N/A	2.70	2.92	3.50	3.90	5.15	6.25
1-7/8"	N/A	3.00	3.22	3.80	4.20	5.45	6.55
2-1/8"	N/A	3.20	3.48	4.00	4.40	5.65	6.75
2-3/8"	N/A	3.45	3.73	4.25	4.65	5.90	7.00
2-5/8"	N/A	3.71	3.99	4.51	4.91	6.16	7.26
2-7/8"	N/A	4.04	4.32	4.84	5.24	6.49	7.59
3-1/8"	N/A	4.23	4.51	5.03	5.43	6.68	7.78
3-1/2"	N/A	4.69	5.03	5.49	5.89	7.14	8.24
3-5/8"	N/A	4.75	5.09	5.55	5.95	7.20	8.30
4-1/8"	N/A	5.26	5.60	6.06	6.46	7.71	8.81
4-1/2"	N/A	5.67	6.01	6.47	6.87	8.12	9.22
5-1/8"	N/A	N/A	6.62	7.08	7.48	8.73	9.83
5-1/2"	N/A	N/A	7.10	7.56	7.96	9.21	10.31
6-1/8"	N/A	N/A	7.73	8.19	8.59	9.84	10.94
6-5/8"	N/A	N/A	8.27	8.73	9.13	10.38	11.48
8-5/8"	N/A	N/A	10.27**	10.73**	11.13**	12.38**	13.48**
10-3/4"	N/A	N/A	12.39**	12.85**	13.25**	14.50**	15.60**
12-3/4"	N/A	N/A	N/A	N/A	15.25**	16.50**	17.60**
14"	N/A	N/A	N/A	N/A	16.53**	17.78**	18.88**
16"	N/A	N/A	N/A	N/A	18.53**	19.78**	20.88**

WARNING:

- Outside diameters (OD) calculated using maximum ID and wall thickness tolerance per ASTM C534 Type I. Actual OD may be smaller.
- This table is provided as a convenience for sizing jacketing materials. It is the responsibility of the installer to determine the correct fit of jacketing materials over AEROFLEX EPDM™ pipe insulation.

*Standard (unslit) tubes only

**Self-Seal tubes only

Revised 111523