



AEROFLEX®

Insulated Pipe Supports



Aerofix®

Insulated Pipe Supports





Aerofix[®]

Insulated Pipe Supports

HVAC | Refrigeration | VRF | Chilled Water
Hot and Cold-Water Piping

Aerofix[®] patented insulated pipe supports are high-strength, load-bearing, closed-cell insulation fittings. Will not compress or crush under loads imposed by active piping systems at pipe hanger and strut clamp locations. Composed of rigid closed-cell, lightweight, polymeric foam and lined with closed-cell EPDM rubber. Aerofix is encased in a zero-perm, weather-proof, corrosion-proof EPDM polymer membrane with a high-performance pressure-sensitive closure system.

Hermetically seals piping against vapor drive. Prevents thermal bridging and the potential for corrosion under insulation (CUI) when installed with AEROFLEX EPDM[™] closed-cell elastomeric pipe insulation, adhesives and zero-perm Protape[®].

Wide range of ID's (1/4" - 12" IPS) and thicknesses (1/2" - 2"). See back cover.

Superior performance

Zero-perm

Hermetic system prevents thermal bridging and corrosion under insulation (CUI)

High-density core maintains thermal efficiency

Wide service temperature range: -328°F to 257°F (-200°C to 125°C)

Safe for indoor environments

Suitable for interior and exterior applications (UV protection required)

Self-extinguishing (ASTM D 635)

No CFC's, HFC's, HCFC's, PBDE's, nitrosamine or fibers

GREENGUARD Gold Certified for low chemical emissions

Environmental Product Declaration (EPD)

Health Product Declaration (HPD)

Naturally mold-resistant; no added biocides required

Ultra-low PVC content — less than 1%



AEROFLEX EPDM[™] insulation system solutions



AEROFLEX[®] Adhesives

Specially formulated adhesives for bonding and vapor-sealing AEROFLEX EPDM[™] insulation. Fast tack and LVOC formulations available.



Protape[®]

Zero-perm EPDM-based, self-adhering rubber tape for sealing glued insulation seams and termination points.



AeroFit[™]

Pre-fabricated insulation fittings made of AEROFLEX EPDM[™] rubber for high-quality installation on HVAC and plumbing piping.



Aerocoat[®]

Premium insulation coating specially formulated for AEROFLEX EPDM[™] insulation to provide UV protection for exterior applications and as a decorative finish.

Fast, simple to install

Ready to install with common pipe hanger types such as trapeze (strut), split-ring, clevis, roller, clamp and strap hangers (refer to AEROFLEX[®] Installation Guide)

Saves labor versus field-applied support methods

Self-sealing and ready for bonding to AEROFLEX EPDM[™] closed-cell elastomeric insulation tubes using AEROFLEX[®] adhesives and Protape[®]

Installation: Scan QR Code on right to view detailed installation guidance for Aerofix Insulated Pipe Supports.



Energy & Atmosphere (EA)	Prerequisite: Minimum Energy Performance Credit: Optimize Energy Performance
Materials & Resources (MR)	Credit: Building Product Disclosure and Optimization - Environmental Product Declarations (EPD), Product Specific Type III Credit: Building Product Disclosure and Optimization - Material Ingredients, verified HPD
Indoor Environmental Quality (EQ)	Credit: Low-Emitting Materials Credit: Indoor Air Quality Assessment Credit: Thermal Comfort Credit: Acoustic Performance
Innovation (IN)	Credit: Occupant Comfort Survey



AEROFLEX®

Nominal 1/2" Wall			
Aerofix ID (inches)	R-Value	Length (inches)	Aerofix OD (inches)
1/4	4.9	3	1.250
3/8	4.4	3	1.441
1/2	4.0	3	1.498
5/8	3.8	3	1.629
3/4	3.6	3	1.757
7/8	3.5	3	1.860
1-1/8	3.3	3	2.297
1-3/8	3.1	3	2.487
1-5/8	3.4	3	2.818
1-7/8	3.3	3	2.980
2-1/8	3.3	3	3.252
2-3/8	3.2	3	3.682
2-5/8	3.1	4	3.862
2-7/8	3.1	4	4.134
3-1/8	2.7	4	4.414
3-1/2	2.7	4	4.780
3-5/8	2.7	4	4.746
4-1/8	2.6	4	5.214
4-1/2	2.6	4	5.682
5-1/2	2.5	4	6.821
6-5/8	2.5	4	7.654
8-5/8	2.5	4	9.784
10-3/4	2.2	4	11.825

Nominal 3/4" Wall			
Aerofix ID (inches)	R-Value	Length (inches)	Aerofix OD (inches)
1/4	7.5	3	1.770
3/8	6.6	3	1.870
1/2	6.1	3	2.009
5/8	5.7	3	2.116
3/4	5.4	3	2.311
7/8	5.2	3	2.406
1-1/8	4.8	3	2.627
1-3/8	4.6	3	3.012
1-5/8	4.9	3	3.393
1-7/8	4.7	3	3.648
2-1/8	4.6	3	3.824
2-3/8	4.5	3	3.990
2-5/8	4.4	4	4.355
2-7/8	4.3	4	4.525
3-1/8	3.8	4	4.817
3-1/2	3.7	4	5.266
3-5/8	3.7	4	5.236
4-1/8	3.6	4	5.936
4-1/2	3.6	4	6.152
5-1/2	3.5	4	7.302
6-5/8	3.4	4	8.357
8-5/8	3.3	4	10.326
10-3/4	3.0	4	12.412

Nominal 1" Wall			
Aerofix ID (inches)	R-Value	Length (inches)	Aerofix OD (inches)
1/4	11.2	3	2.322
3/8	9.9	3	2.462
1/2	9.1	3	2.608
5/8	8.5	3	2.764
3/4	8.1	3	2.908
7/8	7.7	3	2.930
1-1/8	7.2	3	3.252
1-3/8	6.8	3	3.473
1-5/8	6.4	3	3.740
1-7/8	6.2	3	4.080
2-1/8	6.1	3	4.168
2-3/8	5.9	3	4.628
2-5/8	5.8	4	4.792
2-7/8	5.7	4	5.106
3-1/8	4.9	4	5.264
3-1/2	4.8	4	5.714
3-5/8	4.8	4	5.856
4-1/8	4.7	4	6.184
4-1/2	4.6	4	6.566
5-1/2	4.5	4	7.778
6-5/8	4.4	4	8.822
8-5/8	4.3	4	10.710
10-3/4	3.8	4	12.750
12-3/4	3.7	4	15.035

Nominal 1-1/2" Wall			
Aerofix ID (inches)	R-Value	Length (inches)	Aerofix OD (inches)
1/4	15.8	3	3.470
3/8	14.5	3	3.648
1/2	13.6	3	3.652
5/8	12.9	3	3.856
3/4	12.3	3	4.048
7/8	12.0	3	4.050
1-1/8	11.1	3	4.395
1-3/8	10.5	3	4.592
1-5/8	10.0	3	4.834
1-7/8	9.6	3	5.102
2-1/8	9.4	3	5.468
2-3/8	9.1	3	5.504
2-5/8	8.9	4	5.885
2-7/8	8.7	4	6.080
3-1/8	7.6	4	6.372
3-1/2	7.4	4	6.795
3-5/8	7.4	4	6.760
4-1/8	7.2	4	7.204
4-1/2	7.0	4	7.738
5-1/2	6.8	4	8.686
6-5/8	6.6	4	9.872
8-5/8	6.4	4	11.976
10-3/4	5.6	4	14.000
12-3/4	5.5	4	16.000

Nominal 2" Wall			
Aerofix ID (inches)	R-Value	Length (inches)	Aerofix OD (inches)
5/8	18.8	3	4.826
3/4	17.8	3	4.844
7/8	17.0	3	4.994
1-1/8	15.8	3	5.258
1-3/8	14.7	3	5.518
1-5/8	13.9	3	5.726
1-7/8	13.4	3	5.958
2-1/8	13.0	3	6.176
2-3/8	12.6	3	6.556
2-5/8	12.2	4	6.762
2-7/8	12.0	4	7.026
3-1/8	10.4	4	7.332
3-1/2	10.1	4	7.727
3-5/8	10.0	4	7.756
4-1/8	9.7	4	8.292
4-1/2	9.5	4	8.682
5-1/2	9.2	4	9.710
6-5/8	8.8	4	10.755
8-5/8	8.5	4	12.750
10-3/4	7.4	4	14.970
12-3/4	7.2	4	17.000



Aeroflex USA

Sweetwater, TN

www.aeroflexusa.com

082225